

Corning® LSE™ Digital Vortexer

Heavy duty platform-based vortexer

CORNING



The Corning Digital Vortexer is a multipurpose shaker dedicated to a variety of shaking and mixing applications. Three easily removable and interchangeable platforms accommodate many different sample containers such as flasks, bottles, tube racks, plates, boxes, and dishes. The clamp platform has spring loaded retaining bars that adjust to fit vessels of different shapes and sizes. The microplate platform is designed to securely hold up to four microplates. Operation of the vortexer can be timed or continuous, while the speed is variable. The broad speed range allows the vortexer to be used for gentle mixing as well as vigorous agitation. A powerful motor, and a chemically resistant and easy to clean surface makes the equipment a perfect choice for years of trouble-free use.

Features and Benefits

- ▶ Three versatile platform options (available separately)
- ▶ Compact design with easy-access control panel
- ▶ Non-slip rubber mat to keep containers in place
- ▶ Safe for cold room or incubator use
- ▶ Five-year warranty



Specifications

Speed Range	100 to 1,200 rpm
Timer	0 to 99 minutes or continuous
Motion/Orbit Size	Circular, 3 mm
Maximum Load	4.4 lbs. (2 kg)
Ambient Operation Range	+4°C to 65°C
Dimensions (W x D x H)	10.3 x 13.3 x 5.1 in. (26.2 x 33.7 x 13 cm)
Weight	16 lbs. (7.3 kg)
Electrical	115V, 60 Hz 230V, 50 Hz
Warranty	5 years

Ordering Information

Corning® LSE™ Digital Vortexer and Accessories

Cat. No.	Description	Qty
6709	Corning LSE Digital Vortexer, 115V	1
6710	Corning LSE Digital Vortexer, 230V	1
48010	Platform for four microplates	1
48011	Platform with non-slip rubber mat	1
48012	Spring loaded platform for flasks, bottles, or tube racks	1



Platform for four microplates
(Cat. No. 48010)



Platform with non-slip rubber
mat (Cat. No. 48011)



Spring loaded platform for
flasks, bottles, or tube racks
(Cat. No. 48012)

For more specific information on claims, visit the Certificates page at www.corning.com/lifesciences.

Warranty/Disclaimer: Unless otherwise specified, all products are for research use only. Not intended for use in diagnostic or therapeutic procedures. Corning Life Sciences makes no claims regarding the performance of these products for clinical or diagnostic applications.

For additional product or technical information, visit www.corning.com/lifesciences or call 800.492.1110. Outside the United States, call +1.978.442.2200 or contact your local Corning sales office.

CORNING

Corning Incorporated
Life Sciences

836 North St.
Building 300, Suite 3401
Tewksbury, MA 01876
t 800.492.1110
t 978.442.2200
f 978.442.2476

www.corning.com/lifesciences

ASIA/PACIFIC

Australia/New Zealand
t 61 427286832

China
t 86 21 3338 4338
f 86 21 3338 4300

India
t 91 124 4604000
f 91 124 4604099

Japan

t 81 3-3586 1996
f 81 3-3586 1291

Korea

t 82 2-796-9500
f 82 2-796-9300

Singapore

t 65 6572-9740
f 65 6861-2913

Taiwan

t 886 2-2716-0338
f 886 2-2516-7500

EUROPE

CSEurope@corning.com

France

t 0800 916 882
f 0800 918 636

Germany

t 0800 101 1153
f 0800 101 2427

The Netherlands

t 020 655 79 28
f 020 659 76 73

United Kingdom

t 0800 376 8660
f 0800 279 1117

All Other European Countries

t +31 (0) 206 59 60 51
f +31 (0) 206 59 76 73

LATIN AMERICA

grupoLA@corning.com

Brasil

t 55 (11) 3089-7400

Mexico

t (52-81) 8158-8400