LGPv 6520

MediLine



Total gross capacity	601 litre
Ext. dimensions in mm (w/d/h)	700/830/2150
Int. dimensions in mm (w/d/h)	520/700/1550
Energy consumption in 24 h	4,715 kWh
Climate rating ¹	T 5
Cooling system	_
Defrosting	automatic
Temperature range	-10°C to -35°C
Gastronorm	- mm
Housing material/colour	
Door/lid material	Steel
Liner Material	304-grade stainless steel
Type of control	electronic with text display
Temperature display	external digital
Interior light	_
Fault: warning signal	visual and audible
Interface	RS 485
volt-free alarm contact	yes
Shelves	4
Adjustable Shelving	_
Number of drawers	_
Number of baskets	-
Maximum number of baskets	_
Shelf material	grid shelves plastic-coated
Shelf loading	60 kg
Height of adjustable legs	-
Castors/type of castors	yes/swivel castors
Door handle	full-length integrated door handle
Foot pedal opener	-
Self-closing door	yes
Insulation	83 - 60 mm
Defrost water drain	-
Refrigerant	R 290
Airborne acoustical noise emissions	60 dB(A)
Gross/net weight	171,0/143,0 kg
EAN-Nr.	9005382137192

 $1 \quad \text{Climate Ratings: SN } + 10^{\circ}\text{C to } + 32^{\circ}\text{C} \qquad \text{N } + 16^{\circ}\text{C to } + 32^{\circ}\text{C} \qquad \text{ST } + 16^{\circ}\text{C to } + 38^{\circ}\text{C} \qquad \text{T } + 16^{\circ}\text{C to } + 43^{\circ}\text{C}$

Subject to modification. Timestamp: 01.06.2016