

BS 718 : 1991 is generally aligned with ISO 387 and ISO 649. The specification includes five series and three sub-series of hydrometers, of which the most widely used are listed below. They are calibrated using the accepted units of grams per millilitre (g/ml) and are adjusted, except for the “SP” sub-series, at 20°C.

- Series S50** 190mm long, divided in 0.002g/ml, range spans of 0.050g/ml
- Series M50** 270mm long, divided in 0.001g/ml, range spans of 0.050g/ml
- Series L50** 330mm long, divided in 0.0005g/ml, range spans of 0.050g/ml



Range g/ml	To suit Surface Tension	Product Number		
		Series S50	Series M50	Series L50
0.60 to 0.65g/ml	Low	10/300/0	10/330/0	10/360/0
0.65 to 0.70g/ml		10/301/0	10/331/0	10/361/0
0.70 to 0.75g/ml		10/302/0	10/332/0	10/362/0
0.75 to 0.80g/ml		10/303/0	10/333/0	10/363/0
0.80 to 0.85g/ml		10/304/0	10/334/0	10/364/0
0.85 to 0.90g/ml		10/305/0	10/335/0	10/365/0
0.90 to 0.95g/ml		10/306/0	10/336/0	10/366/0
0.95 to 1.00g/ml		10/307/0	10/337/0	10/367/0
1.00 to 1.05g/ml	Medium	10/308/0	10/338/0	10/368/0
1.05 to 1.10g/ml		10/309/0	10/339/0	10/369/0
1.10 to 1.15g/ml		10/310/0	10/340/0	10/370/0
1.15 to 1.20g/ml		10/311/0	10/341/0	10/371/0
1.20 to 1.25g/ml		10/312/0	10/342/0	10/372/0
1.25 to 1.30g/ml		10/313/0	10/343/0	10/373/0
1.30 to 1.35g/ml		10/314/0	10/344/0	10/374/0
1.35 to 1.40g/ml		10/315/0	10/345/0	10/375/0
1.40 to 1.45g/ml		10/316/0	10/346/0	10/376/0
1.45 to 1.50g/ml		10/317/0	10/347/0	10/377/0
1.50 to 1.55g/ml		10/318/0	10/348/0	10/378/0
1.55 to 1.60g/ml		10/319/0	10/349/0	10/379/0
1.60 to 1.65g/ml		10/320/0	10/350/0	10/380/0
1.65 to 1.70g/ml		10/321/0	10/351/0	10/381/0
1.70 to 1.75g/ml		10/322/0	10/352/0	10/382/0
1.75 to 1.80g/ml		10/323/0	10/353/0	10/383/0
1.80 to 1.85g/ml		10/324/0	10/354/0	10/384/0
1.85 to 1.90g/ml		10/325/0	10/355/0	10/385/0
1.90 to 1.95g/ml	10/326/0	10/356/0	10/386/0	
1.95 to 2.00g/ml	10/327/0	10/357/0	10/387/0	

Series M100

Adjusted at 20°C, these hydrometers have a range span of 0.100g/ml with a length of 250mm and are divided every 0.002g/ml.

Range g/ml	To suit Surface Tension	Product Number
0.60 to 0.70g/ml	Low	10/400/0
0.70 to 0.80g/ml		10/401/0
0.80 to 0.90g/ml		10/402/0
0.90 to 1.00g/ml		10/403/0
1.00 to 1.10g/ml	Medium	10/404/0
1.10 to 1.20g/ml		10/405/0
1.20 to 1.30g/ml		10/406/0
1.30 to 1.40g/ml		10/407/0
1.40 to 1.50g/ml		10/408/0
1.50 to 1.60g/ml		10/409/0
1.60 to 1.70g/ml		10/410/0
1.70 to 1.80g/ml		10/411/0
1.80 to 1.90g/ml		10/412/0
1.90 to 2.00g/ml		10/413/0